

simplifi

4G LTE Wireless Router

CONNECTI



Top Features Included Right Out of the Box



Plug N Play

Just plug into an outlet and



Captive Portal

Collect network user emails for



Failover Built-In
Use Connect cellular back-up
when primary goes down.



Secure Network
VPN, cellular encryption, block



Remotely manage everything from a single pane of glass.





For More Information, Contact:

CONNECTI simplifi





Super-charge Your Network With Simplifi Connect II 4G LTE Router!



Seamless POTS line replacement over VoLTE with Simplifi Voicelink Smart Dongle

Ready to Make the Change? www.simplifi.io/connect

Networks	BS6425I -AF-11
Networks	LTE FDD: B2/B4/B5/B12/B13/B14(FirstNet)/B66/B71
	WCDMA: B2/B4/B5
	BS6425L-A-11 LTE FDD: B2/B4/B12
	WCDMA: B2/B4/B5
	BS6425L-V-11 LTF FDD: B4/B13
Data Speeds	LTE - FDD CAT4 Max150Mbps (DL), Max 50Mbps (UL)
	DC-HSPA+ DL 42 Mbps HSUPA - UL 5.76Mbps
	1130FA - OL 3.7 ONIDPS
WLAN	Dual-Band/802.11 b/g/n/ac, WPA / WPA2/WPA2 Enterprise
USB (3.0)	USB (Host) HS and FS
LAN (100) (1000 P T)	RJ-45 Modular Jack on side panel for TCP / IP, PPP, UDP
(10/100/1000 Base-T)	
SIM	1.8V and 3.0V standard USIM (2FF)

LED Indicators	Cellular network status (1 ea.) LAN traffic (1 ea.) USB traffic (1 ea.)
Power Supply Requirements	120 /240 VAC at 10VA (10W) max
Outline Dimensions (Less AC prongs and mounting tab)	4.1" (104mm) Height 2.2" (56mm) Width 2.0" (51mm) Depth
Weight	7 oz (198 g)
Operating Temperature	-10°C to +40°C
Storage Temperature	-30°C to +70°C
Approvals	PTCRB, 3GPP FCC parts 2 and 15 CE, TUV
Cellular Carrier Approvals	AT&T, FirstNet, T-Mobile, UScellular, and Verizon
Patents	US Patent Nos. 8676254, 9402326, 9485116 with other US and international patents pending.

