



Manage Centrally With No Additional Hardware Needed

SSID Management

SSID	Security	SSID Visibility	Radio Selection
Production	WPA2 - Personal	✓	2.4 GHz band only
_Guest_43	WPA2 - Personal	✓	2.4 GHz band only
_Guest_50	WPA2 - Personal	✓	5 GHz band only
Production_11a	WPA2 - Personal	✓	5 GHz band only
Wholesale	WPA2 - Personal	✓	2.4 GHz band only
Wholesale_11a	WPA2 - Personal	✓	5 GHz band only
Balance	WPA2 - Personal	✓	2.4 GHz band only
Balance_11a	WPA2 - Personal	✓	5 GHz band only

Usage Report

Usage Reports

Data Usage: Hourly Daily Monthly Line MB GB TB

Device Selection: All By products By tags

Daily Report

Daily Usage

3960.63 GB

195.31 GB

0 GB

Download Upload Total

Day	Download	Upload	Total
2020-07-13	32.90 GB	17.21 GB	70.11 GB
2020-07-12	14.86 GB	0.67 GB	15.54 GB
2020-07-11	15.34 GB	0.67 GB	16.01 GB

Searchable Event Log

Search & Filter

Type: Details

- system: Time synchronization successful
- system: Time synchronization fail
- system: Time synchronization successful
- system: Time synchronization fail
- system: Changes applied
- system: Changes applied
- system: Changes applied
- system: InControl has updated the configuration as logs were updated
- system: WPA2 Configuration has been updated by InControl
- system: InControl has updated the configuration as 100 wire updates


MSRP: \$299

AP One AX Lite comes equipped with InControl central management. Giving users the ability to control and monitor their network from any web browser. Manage network SSIDs, radio settings, and search event logs with ease to diagnose the entire network.



For More Information, Contact:



Turnkey or Custom Captive Portals



Offer users a more branded experience by customizing captive portals through InControl.



Wi-Fi Just Got Better

Integrated Wi-Fi 6 is 45% faster than the average Wi-Fi 5, has 4 more device capacity and consumes less power for connected devices.

Enterprise-Grade Roaming Speeds
Supports 802.11k/v/r, providing users a seamless roaming experience between access points.



Seamless Peplink SD-WAN Integration

Effortlessly integrate Peplink solutions with **AP One AX Lite** to provide unique network capabilities and network flexibility, making the whole experience more user friendly.

Centrally Managed with InControl

Monitor network health on a single dashboard. Push configuration profiles on multiple devices at once. Remotely access the Web Admin of any device.

Balance/MAX/FusionHub


Provides unbreakable connectivity by combining multiple WANs. Works with InControl to centralize VLAN, firewall, and outbound policies.

SD-Switch


Works with InControl to remotely configure and activate PoE ports. Monitor power consumption.

AP One

Works with InControl to centralize SSIDs, radio settings, and deliver captive portals.



AP One AX Lite



Specifications

Ethernet Ports	1 x 1Gbps Gigabit Ethernet
Wi-Fi Standard	Simultaneous 1 x 2.4GHz 802.11b/g/n/ax 1 x 5GHz 802.11a/n/ac/ax
Radio Chains/Streams	2 x 2:2
Data Rates	2.4 GHz: up to 574 Mbps 5 GHz: up to 1200 Mbps
Channel Width	20/40/80 MHz
Recommended clients per Radio	256
SSID Per Radio	16
Transmit Power	2412 – 2472 MHz: 24dBm 5180 – 5825 MHz: 25dBm
Antenna	Built-in Omni antenna: 2 x 3dBi - 2.4GHz 2 x 3dBi - 5GHz
Enclosure	Plenum-rated enclosure
Dimensions	5.9 x 5.9 x 1.3 inches 160 x 160 x 33 mm
Weight	0.84 pounds / 382 grams
Power Input	12V DC Jack (Plug 5.5 x 2.1 mm, center positive)* 802.3at PoE*
Power Consumption	14.5W (max.)
Operating Temperature	32°F - 104°F 0°C - 40°C
Certifications	FCC, CE, RoHS
Warranty	1 Year Limited Warranty

Network	Bridge Mode Router (NAT) Mode Mesh Wireless Distribution System (WDS) Support for PPPoE, Static IP, DHCP Management VLAN Spanning Tree Protocol
Radio	Multiple SSID Auto Channel Selection Transmit Power Adjustment Neighbor AP Detection
AP Security	Open WPA/WPA2/WPA3-Personal WPA/WPA2-Enterprise
Device Management	Web Administrative Interface InControl Cloud Management Peplink AP Controller SNMP v1, v2c and v3
Client Management	Per SSID VLAN with QoS (802.1p/802.1q) Bandwidth Control MAC Address Filtering Layer 2 Client Isolation Limit on Max. Number of Clients
	Per Client VLAN with RADIUS VLAN with VLAN Pool Bandwidth Control Multicast Filter IGMP Snooping/Multicast Enhancement
Captive Portal by InControl	
Package Contents	AP One AX Lite, Ceiling Mount Base (9/16" T-Rail), Ceiling Mount Base (15/16" T-Rail), Mounting Screw Set

* AC/DC adapter and PoE Injector are not included.

Ordering information

Product Code	Description
APO-AX-LITE	2 x 2 MU-MIMO Wi-Fi 6 AP for business, manageable by InControl. Simultaneous Dual-Band 802.11ax/ac/b/g/n

Feature Add-on

Product Code	Description
ACW-107	802.3af/at PoE Injector. Compatible with MAX Hotspot and AP One AX Series
ACW-602	1x12V3A Power Supply. Compatible with MAX HD2 and AP One AX Series