







Unbreakable Connectivity with 5G

The Balance 310X provides built-in 5G for seamless failover. Patented SpeedFusion technology combines multiple connections for jitter-free calls and high-speed transfers.

Traffic Steering

Like many of our products, the Balance 310X 5G integrates our feature, Traffic Steering. Allowing users to manage and switch to the most suitable connection as bandwidth changes.

For More Information, Contact:









Balance 310X 56^h



Specifications

WAN Interface	1x Embedded 5G Modem with Redundant SIM Slots 2x 10/100/1000M Ethernet 2x USB 2.0 Interface	Power Consumption	30W (max.)
		Dimensions	1.7 x 11.5 x 7.0 inches 43 x 292 x 177 mm
LAN Interface	9x 10/100/1000M Ethernet	Weight	7.28 pounds 3.3 kg
Router Throughput	2.5 Gbps	Operating Temperature	-40° – 149 °F -40° – 65 °C
PepVPN Throughput (No Encryption)	600 Mbps	Humidity	15% – 95% (non-condensing)
PepVPN Throughput	500 Mbps	Certifications	FCC, CE, RoHS
(256-bit AES) 5G Cellular Data Rate® (Downlink/Uplink)	5G: 4 Gbps / 700 Mbps LTE CAT-20: 2 Gbps / 150 Mbps	Package Content	Balance 310X 5G, 1x PSU 24V 2.5A (ACW-647), 4x LTE/5G Antennas (ACW-235) 1x GPS Antenna (ACW-232), 1 Pair of Mounting Brackets (ACW-513)
Recommended Users	50-500		Rubber Foot Pad Set, Grounding Cable
Antenna Connectors	4x SMA Cellular Antenna Connectors 1x SMA GPS Antenna Connector	Warranty	1-year Limited Warranty
Power Input	Power Din DC: 12V – 30V		

[@]Theoretical maximum data rates

Ordering information

Product Code	Embedded Modem	Regions	5G Bands	LTE Bands
BPL-310X-5GD-T	1x 5G	Primary: APAC, EMEA Compatibility: Global	Cellular 1: 5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n7, n8, n12, n20, n28, n38, n41, n66, n71, n77, n78, n79	Cellular 1: B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71
BPL-310X-5GH-T	1x 5G	Primary: North America* Compatibility: Global	Cellular 1: 5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n28, n41, n66, n71, n77, n78, n79	Cellular 1: B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32,B34, B38, B39, B40, B41, B42, B46, B48, B66, B71

^{*} US Carrier Certifications: AT&T, T-Mobile, US Cellular, Verizon

www.pwbts.net 281-667-0404





Expansion Module for B310X 5G



Specifications

Interface	1x Embedded Cellular Modems with Redundant SIM Slots	Dimensions	0.9 x 11.5 x 3.5 inches 22 x 292 x 88 mm
Antenna Connectors	4x SMA Antenna Connectors, 1x SMA GPS Antenna Connector	Weight	2.2 pounds 1 kg
5G Cellular Data Rate® (Downlink/Uplink)	5G: 4 Gbps / 700 Mbps LTE CAT-20: 2 Gbps / 150 Mbps		

Ordering information

Product Code	Description	Embedded Modem	Carrier/Categories	5G Bands	LTE Bands
EXM-310X-5GD	Expansion Module for B310X with 1x 5G modem	1	Primary: APAC, EMEA Compatibility: Global	5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n7, n8, n12, n20, n28, n38, n41, n66, n71, n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71
EXM-310X-5GH	Expansion Module for B310X with 1x 5G modem	1	Primary: North America* Compatibility: Global	5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n28, n41, n66, n71, n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71

^{*} US Carrier Certifications (Pending): AT&T, T-Mobile, US Cellular, Verizon

@Theoretical maximum data rates

Available globally. Regional and carrier certification is subject to local approval.

www.pwbts.net 281-667-0404