



Built to last

Sturdy industrial-strength designed for continuous high-traffic operation.



Stay Connected

With two SIM slots and an eSIM, the MAX Adapter always has a way to connect.

MAX ADAPTER
State-of-the-art Cellular Modem at a breakthrough price point

MSRP: \$649



Portable

The light and sleek enclosure offers portability in the palm of your hands.

Compatible with 5G

MAX Adapter now offers a 5G compatible device option. Bringing 5G connectivity to your devices.



For More Information, Contact:

Connect with



Peplink Products

Protect and reinforce products^ with a USB port and make it a 5G/LTE WAN.

 [Learn More](#)

OR

Windows & Linux* Devices

Providing 5G/LTE connectivity for Windows and Linux devices on-the-go.



peplink | PEPWAVE
MAX Adapter 5G



Specifications

Cellular WAN Interfaces	Single 5G Modem	Operating Temperature	32° – 104°F / 0° – 40°C
Redundant SIM Slot	Yes	Humidity	15% – 95% (non-condensing)
Downlink/Uplink Datarate	5G: 4 Gbps / 700 Mbps LTE CAT-20: 2 Gbps / 150 Mbps	Warranty	1-Year Limited Warranty
Antenna Connectors	4x SMA Cellular	Certifications	FCC, CE, IC
Power Input	5V USB-C	Package Content	MAX Adapter 5G, 4x LTE/5G LTE Antennas (ACW-235), USB-C Female to USB-A Male Adapter, USB-C Power Cable
Power Consumption	5W (nominal), 8W (max.)	US Carrier Certifications	AT&T, T-Mobile, US Cellular
Dimensions	3.9 x 2.8 x 0.6 inches / 100 x 71 x 15 mm		
Weight	120g		

Ordering information

Product Code	Carrier / Category	5G Bands	LTE Bands
MAX-ADP-5GH-T	Global / 5G	5G (NSA) Sub 6Ghz: n1, n2, n3, n5, n28, n41, n66, n71, n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B46, B48, B66, B71

peplink | PEPWAVE
MAX Adapter 5G



Specifications

Cellular WAN Interfaces	Single LTE Modem	Weight	120g
Redundant SIM Slot	Yes	Operating Temperature	32° – 104°F / 0° – 40°C
Downlink/Uplink Datarate	CAT-12: 600 Mbps / 150 Mbps CAT-6: 300Mbps / 50Mbps	Humidity	15% – 95% (non-condensing)
Antenna Connectors	2x SMA Cellular, 1x SMA GPS	Warranty	1-Year Limited Warranty
Power Input	5V USB-C	Certifications	FCC, CE, IC
Power Consumption	5W (nominal), 8W (max.)	Package Content	MAX Adapter, 2x LTE Antennas (ACW-813), USB-C Female to USB-A Male Adapter, USB-C Power Cable
Dimensions	3.9 x 2.8 x 0.6 inches / 100 x 71 x 15 mm	US Carrier Certifications	Verizon, AT&T

Ordering information

Product Code	Carrier / Category	LTE Bands	3G Bands
MAX-ADP-LTEA-K-T	Global CAT-12	B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B18, B19, B20, B26, B28, B29, B30, B32, B41, B42, B43, B46, B48, B66	HSPA+: B1, B2, B4, B5, B6, B8, B9, B19
MAX-ADP-LTEA-R-T	America / FirstNet CAT-12	B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B14, B18, B19, B20, B26, B29, B30, B32, B41, B42, B43, B46, B48, B66	HSPA+: B1, B2, B4, B5, B6, B8, B9, B19
MAX-ADP-LTEA-W-T	Global CAT-6	B1, B2, B3, B4, B5, B7, B8, B12, B13, B20, B25, B26, B29, B30, B41	WCDMA/HSPA+/DC-HSPA+: B1, B2, B3, B4, B5, B8

Accessories

Product Code	Description
ACW-232	GPS Antenna